

Strut Mounted Fixed Point Anchor M10






Product Description

Designed to stop axial, lateral and vertical movement of pipe.

These can be floor or ceiling mounted and are suitable for connections to Strut profiles.

Design Features

- Double M10 Connections to pipe clips
- Electro Painted, Zinc or Zinc Nickel Finish
- Specially designed for use on strut profiles
- Supplied with BZP Clips
- Recommended that Pipe Stops are used, please refer to install instructions



Part Number	Clip to fit pipe OD (mm)	Connection	Load Axial	Load Vertical	Load Lateral	Max Temp	Dist (Strut to pipe centre)
NS-LWFA-15NB	20-24	2x M10	2.5kN	2.5kN	2.5kN	200	52.1mm
NS-LWFA-20NB	25-30	2x M10	2.5kN	2.5kN	2.5kN	200	50.5mm
NS-LWFA-25NB	31-35	2x M10	2.5kN	2.5kN	2.5kN	200	54.9mm
NS-LWFA-32NB	40-45	2x M10	2.5kN	2.5kN	2.5kN	200	60mm
NS-LWFA-40NB	48-58	2x M10	2.5kN	2.5kN	2.5kN	200	64mm
NS-LWFA-50NB	60-65	2x M10	2.5kN	2.5kN	2.5kN	200	70mm